

DIRECT-REPLACEMENT
INSTALLATION GUIDE



SUPER DUTY F250/F350 (05+)

2.0 Performance Series Reservoir (LSC)

2.5 Factory Series Reservoir (DSC)



SUPER DUTY F250/F350 (05+)

985-24-161: 2.0 Performance Series Reservoir

985-26-161: 2.0 Performance Series Reservoir (LSC)

985-24-162: 2.0 Performance Series Reservoir

985-26-162: 2.0 Performance Series Reservoir (LSC)

985-24-163: 2.0 Performance Series Reservoir

985-26-163: 2.0 Performance Series Reservoir (LSC)

883-24-040: 2.5 Factory Series Reservoir

883-26-040: 2.5 Factory Series Reservoir (DSC)

883-24-041: 2.5 Factory Series Reservoir

883-26-041: 2.5 Factory Series Reservoir (DSC)

883-24-042: 2.5 Factory Series Reservoir

883-26-042: 2.5 Factory Series Reservoir (DSC)

883-24-043: 2.5 Factory Series Reservoir

883-26-043: 2.5 Factory Series Reservoir (DSC)

883-24-044: 2.5 Factory Series Reservoir

883-26-044: 2.5 Factory Series Reservoir (DSC)

883-24-045: 2.5 Factory Series Reservoir

883-26-045: 2.5 Factory Series Reservoir (DSC)

883-24-046: 2.5 Factory Series Reservoir

883-26-046: 2.5 Factory Series Reservoir (DSC)

883-24-047: 2.5 Factory Series Reservoir

883-26-047: 2.5 Factory Series Reservoir (DSC)

883-24-048: 2.5 Factory Series Reservoir

883-26-048: 2.5 Factory Series Reservoir (DSC)

SAFETY INSTRUCTIONS

WARNING

Thank you for choosing FOX direct-replacement shocks for your vehicle. FOX products are designed, tested, and manufactured by the finest professionals in the industry.

FOX recommends that you become completely familiar with the handling characteristics of your modified vehicle before operating it under rigorous conditions, helping to avoid potential rollover situations and other loss of control events. FOX further recommends that you use appropriate protective equipment at all times when operating your vehicle.

To achieve the best performance and product longevity, periodic service and maintenance is required. Please refer to the Service and Upgrades section for more information.

- FOX direct-replacement shocks are designed to fit and allow proper clearance with the stock suspension. If aftermarket suspension components are installed it is the customers responsibility to ensure that at full cycle the suspension clears the FOX shocks.
- FOX direct-replacement shocks should always be installed as a pair for maximum performance.
- Proper installation and service procedures are essential for the safe and reliable installation of chassis parts, requiring the experience and tools specially designed for this purpose. Installation and maintenance procedures for this product must be performed by a qualified service technician, to avoid potentially unsafe vehicle handling characteristics, which may result in **SERIOUS INJURY** or **DEATH**.
- Modifying your vehicle's suspension will change the handling characteristics of your vehicle. Under certain conditions,



your modified vehicle may be more susceptible to loss of control or rollover, which can result in **SERIOUS INJURY** or **DEATH**. Thoroughly familiarize yourself with the modified vehicle handling characteristics before any rigorous vehicle operation. Wear body protective gear including head protection when appropriate. Installation of vehicle roll bars or cage is highly recommended.

- FOX direct-replacement shocks are gas-charged and are highly pressurized. Placing shocks in a vise or clamp, applying heat, or attempting to open or service the shock without the proper tools and training can result in **SERIOUS INJURY** or **DEATH**. Do not attempt to modify, puncture or incinerate a FOX direct-replacement shock absorber.
- Any attempt to misuse, misapply, modify, or tamper with any FOX product voids any warranty and may result in **SERIOUS INJURY** or **DEATH**.

INSTALLATION GUIDELINES

WARNING

- Always use a chassis lift for the installation of shocks, and make certain that the raised vehicle is securely attached to the lift to prevent the vehicle from slipping, falling, or moving during the installation process.
- **DO NOT** install any FOX product without the necessary special tools, expertise and chassis lift, or you will subject yourself to the risk of **SERIOUS INJURY** or **DEATH**. If you elect to not use a chassis lift (which election may result in **SERIOUS INJURY** or **DEATH**), ensure that the vehicle is on level ground, that all tires on the ground during installation are blocked to prevent vehicle movement, that at least two tires are on the ground at all times, and that adequately secured jack stands are used to support the vehicle. **NEVER** get under the vehicle until you have checked to ensure that the vehicle will be stable during installation.
- FOX direct-replacement shocks are designed to fit your vehicle's shock mounts with no modifications with the

exception of reservoir placement on specific models and applications.

INSTRUCTIONS - FRONT

Medium-strength thread locker (blue) is recommended on all bolts.

1. Please read the installation guidelines for instructions on how to properly lift and secure the vehicle.
2. Remove both front wheels.
3. Remove the stock shocks. (Do not discard lower stock hardware, as it will be used with your new FOX shock.)
4. Install new FOX shock. With external reservoir models, make sure that the hoses are facing outward and toward rear of the vehicle. (Fig. 1a,1b)
5. Connect shock to upper mount with supplied stem mount washer and bushing on each side. Tighten nut until 5/8" of total stem is showing.
6. Connect shock to lower mount reusing stock hardware. Torque to OEM specification.



Fig. 1a: 2005-2016 Driver Side



Fig. 1b: 2017+ Passenger Side

7a. 2005-2016 Models ONLY:

Install supplied reservoir brackets onto the vehicle frame as shown. Mark the lower bracket hole approximately 2.5" from the edge of the shock tower toward the rear of the vehicle and 4" from the bottom of the frame. Drill a 7/32" pilot hole, then secure the reservoir bracket to the frame with one of the supplied 1/4" self tapping screws. Repeat marking and drilling the center hole and installing self tapping screw. (Fig. 2a)

7b. 2017+ Models ONLY:

Install supplied reservoir brackets onto the vehicle frame as shown. Mark the lower bracket hole approximately 4.5" from the edge of the shock tower toward the rear of the vehicle and 4" from the bottom of the frame. Drill a 7/32" pilot hole, then secure the reservoir bracket to the frame with one of the supplied 1/4" self tapping screws. Repeat marking and drilling the center hole, then install self tapping screw. (Fig. 2b)



Fig. 2a: 2005-2016 Driver Side




Fig. 2b: 2017+ Passenger Side

8. External Reservoir Models:

Mount the reservoir onto the reservoir bracket with the supplied hose clamps. Utilize the slots in the brackets to locate clamps. Do not feed the clamps through the slots in the brackets. (Fig. 1a,1b)

9. Check that suspension has proper clearance by steering in both directions.
10. Reinstall front wheels and torque to OEM specifications.

INSTRUCTIONS - REAR




Medium-strength thread locker (blue) is recommended on all bolts.

1. Please read the installation guidelines for instructions on how to properly lift and secure the vehicle.
2. Remove the stock shocks. It may be necessary to support or raise the vehicle axle in order to remove bolts and for installation of new FOX shock. (Do not discard stock hardware, as it will be used with your new FOX shock.)
3. Install supplied rubber spacer onto upper post mount.
4. Install new FOX shock, reusing stock hardware. For piggyback reservoir models, make sure the reservoir is pointed inward on the driver side and toward the rear of the vehicle on the passenger side (Fig. 3). Torque to OEM specifications.



Fig 3

FOX FACTORY SETTING





FOX LIMITED WARRANTY

FOX Factory, Inc., a California corporation having offices at 130 Hangar Way, Watsonville, CA 95076 ("FOX"), makes the following LIMITED WARRANTY with respect to its suspension products:

LIMITED ONE (1) YEAR WARRANTY ON SUSPENSION PRODUCTS

Subject to the limitations, terms and conditions hereof, FOX warrants, to the original retail owner of each new FOX suspension product, that the FOX suspension product, when new, is free from defects in materials and workmanship. Unless otherwise required by law, this warranty expires one (1) year from the date of the original FOX suspension product retail purchase from an authorized FOX dealer or from a FOX authorized Original Equipment Manufacturer where FOX suspension is included as original equipment on a purchased vehicle. If law requires a warranty duration of greater than one (1) year, then, subject to the other provisions hereof, this warranty will expire at the end of the minimum warranty period required by such law.

TERMS OF WARRANTY

This warranty is conditioned on the FOX suspension product being operated under normal conditions and properly maintained as specified by FOX. This warranty is only applicable to FOX suspensions purchased new from an authorized FOX source and is made only to the original retail owner of the new FOX suspension product and is not transferable to subsequent owners. This warranty is void if the FOX suspension product is subjected to abuse, neglect, improper or unauthorized repair, improper or unauthorized service or maintenance, alteration, modification, accident or other abnormal, excessive, or improper use.

Should it be determined by FOX in its sole and final discretion, that a FOX suspension product is covered by this warranty, it will be repaired or replaced, by a comparable model, at FOX's sole option, which will be conclusive and binding. **THIS IS THE EXCLUSIVE REMEDY UNDER THIS WARRANTY. ANY AND ALL OTHER REMEDIES AND DAMAGES THAT MAY OTHERWISE BE APPLICABLE ARE EXCLUDED, INCLUDING, BUT NOT LIMITED TO,**

INCIDENTAL OR CONSEQUENTIAL DAMAGES OR PUNATIVE DAMAGES.

This limited warranty does not apply to normal wear and tear, malfunctions or failures that result from abuse, improper assembly, neglect, alteration, improper maintenance, crash, misuse or collision. This limited warranty gives the consumer specific legal rights. The consumer may also have other legal rights which vary from state to state or country to country. Some states and countries do not allow the exclusion or limitation of incidental or consequential damages or warranties, and if dictated by law the above limitations or exclusions may not apply to you. If it is determined by a court of competent jurisdiction that a certain provision of this limited warranty does not apply, such determination shall not affect any other provision of this limited warranty and all other provisions shall remain in full effect.

THIS IS THE ONLY WARRANTY MADE BY FOX ON ITS SUSPENSION PRODUCTS AND COMPONENTS, AND THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION HEREIN. ANY WARRANTIES THAT MAY OTHERWISE BE IMPLIED BY LAW INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXCLUDED.



**SHOX NEED
♥ TOO**



FOX SERVICE & UPGRADES

Have your FOX serviced or upgraded by FOX technicians. Call our Off-Road and Truck Service Center at 619.768.1800 to go over the service and upgrade options available for your shocks. Once you've setup your service or upgrades you will receive a return authorization number and shipping instructions.

COMPLETE SERVICE INTERVALS

- 100% street use: every 50,000 miles
- 50% street / 50% off-road use:
every 10,000 miles

SERVICE MENUS & PRICING

Visit ridefox.com/orservice



RIDEFOX.COM 750 VERNON WAY SUITE 101. EL CAJON, CA 92020 USA
1.800.FOX.SHOX (369.7469) 619.768.1800 ORSERVICE@RIDEFOX.COM
PN 605-01-224 REV B JULY 2018